

Last Modified on 02/12/2019 4:11 pm EST

- 1. Press the **Setup** key on the keyboard
- 2. Click Print/Network
- 3. Click Global Configuration tab
- 4. Within Devices, Add a New Device
- 5. Select DICOM Archive Server in the Step 1 drop down

| Printer/ Device Global Network Capture Selection Config | | |
|---|--|---|
| System | Devices HD Maint. | |
| - Device Configuration | | -NEW SYNGO |
| | Name | Configuration: DICOM Archive Serve |
| NEW SYNGO PACS BACKUP PHILIPS PACS TRICE PATIENT ViewPoint Images | DICOM Archive Server DICOM Archive Server DICOM Archive Server DICOM Archive Server DICOM Archive Server | AE Title: WN54001 Port #: 104 IP Address:170.173.221.38 |
| VIEWPOINT | Step 1: Select the device type DICOM Archive Server Step 2: Configure the new device | |

- 7. Configure the first new device (long term medical image store) as:
 - -Alias or Name = Trice Archive
 - -AE Title = archive

-Port = 104 (or what was input during uplink setup)

- -IP Address = x.x.x.x refer to the computer running Uplink
- 8. Configure the next new device (texting/email patients) as:

-Alias or Name = Trice Patient

-AE Title = archive

-Port = 104 (or what was input during uplink setup)

- -IP Address = x.x.x.x refer to the computer running Uplink
- 9. Activate the New Device by clicking Device Selection
- 10. Click Archive
- 11. Check the active Archive Servers for Trice





12. Save and Done

*Click here for instructions on determining the correct port.

Click here for instructions on testing the configuration of your machine.

Note: The machine cannot be in Exam Mode during configuration.